



# DERBYDOG INC

DEMOLITION DERBY

## PRO STOCK MINIS

2/20/25

**-RULES SUBJECT to CHANGE at ANYTIME-**

### GENERAL

1. Maximum wheelbase 110" FWD or RWD. No full-size cars permitted. Mid-size or compact cars ONLY.
  2. Helmet, seat belt, and eye protection must be worn at all times. Any controversies or protests must be brought up during the drivers meeting.
  3. Any questions call first if it doesn't say you can, don't do it. Cars must be stock unless modification is stated in the rules. No painting of the frames. Judges' decisions are final. All cars are subject to re- inspection at any time before, during, or after the event no refunds on illegal cars. We have the right to re-inspect, cut, or drill any car at any time. If you are caught breaking the rules set here forth you will forfeit any and all winnings and or prizes you are due.
  4. All glass, plastic, and interior must be removed before arriving to the event. Cars must be stock unless modifications stated in rules. We have the right to re-inspect, drill, or cut any car at any time. If you stretch a rule, you will lose that rule.
- 

### BODY

1. Doors may be welded all the way around on the outside of the body only with ¼" x 3" wide strapping no excessive overlapping of strapping is permitted. No welding or plating on the inside of doors. A door skin is permitted from front seam on driver's door to rear seam on driver's door.
2. Deck lids and tailgates may be welded with a 5" on 5" off rule using ¼" x 3" wide pieces of steel or 9 wired or banding in 8 spots. Deck lids and tailgates must be in original location. Rear of deck lids may be folded down in the trunk, Trunk lids may be dipped along with speaker deck. If speaker deck is removed trunk lid can only be welded to quarter panels and tail light assembly only nothing may be welded inside of trunk. Deck lids must be factory for make and model of car.
3. Hood may be 9 wired in 8 places or bolted in 6 places bolts may be 5/8" in dia. front 2 body mounts may extend through core support and used as front 2 of the 6 hood bolts 1" all thread max you cannot sleeve the all thread with anything from top of frame to top of core support. A 12" hole minimum must be in the hood.
4. No interior body seam welding will be permitted. Doors can be welded on outside of body only. On pre-ran cars the doors may be repaired back to stock. Rust repair is limited to floor boards and roofs only. Patch metal cannot exceed factory thickness. Rust holes must be visible if patching is done.
5. You may have a window bar or wire in windshield and rear window. Metal can be no thicker than 3/8" and no wider than 3" you may use 2 x 2 pipe. Not solid. They can be welded to roof and firewall no more than 6" from the window area. And welded to the floor directly above rear axle the rear window bar cannot be attached to anything else except for roof of car and floor pan and welded 6" at the rear window on roof and 6" on floor pan. Rollover bar may attach to front window bar and rear window bar but cannot exceed past the main portion of cage.
6. Hoods must be open for inspection. (12" x 12" hole over carburetor).
7. Cars may not be smashed flat if cars are tucked the rear quarter panels must stay at the factory height deck lids must be in factory location (above rain channels).

8. You can add a piece of angle (4" x 4" x ¼"max.) to top of the core support but can be no longer than 1" wider than the radiator no other metal permitted on core support except a radiator guard in front of radiator with (4) 2" welds to mount it. No radiator protectors or holders are permitted. No other metal permitted to be welded to core support.
  9. Original gas tank may be removed and replaced with a boat-type tank or fuel cell Moved inside of car behind driver's seat but no further back than rear axle. If fuel tank is in front of rear axle you may leave it in stock location. No stock fuel tanks permitted inside of car. Batteries must be moved to passenger side floor board and securely fastened.
  10. No wire or straps can attach roof to floor in rear seat area.
  11. Aftermarket pedals, shifter, transmission coolers are all permitted but cannot strengthen car in anyway.
  12. No wire or straps can attach from roof to floor.
- 

### **CAGE**

1. You may have a 4-point cage surrounding the drivers compartment with a roll over bar. Bars 6" diam. Max must be sheet metal to sheet metal only. Dash bar must be 5" away from all sheet metal, the bar behind the seat can sit no further back than 12" from rear of driver's seat and must be at least 5" off the floor measured from the highest part of the floor/ driveshaft tunnel. You may use a rollover bar from front side of roll bar across the roof down to dash bar this may not connect to sheet metal. Door bars may be no farther forward than the firewall and extend into rear doors on 4 door cars they must stop 2" from back of door on 2 door cars they must stop 3" from rear wheel well on the body the rear of these bars must be free floating and may not attach to body.
  2. No angling of roll over bars permitted.
  3. You may have gussets in cage at the corners. They must be within 6" of corners of bars only no other gussets will be permitted.
  4. You may use 2 down legs to the frame from the rear bar down to frame these must run straight down no angling of the down legs permitted.
  5. You may use a floating gas tank protector that comes off the back bar but it cannot be wider than 24" The gas tank protector or holder may go all the way back to the sheet metal. The gas tank protector must stop at the sheet metal in front of rear axle and rear seat meet. Gas tank protector rear bars must go straight up, (no angling bars over speaker deck)
  6. A center bar from rear seat bar to dash bar is permitted. You may use a bar from the roll over bar on roof across the front roof down to dash bar. Door bars may not extend farther forward than the firewall.
- 

### **FRAME**

1. Trailer hitches and braces must be removed. No plating, pinning, heat treating, stuffing the frame of any kind. Do not paint frame! No welds on frame or K member may exceed a single pass no weave passes or building the weld up will be permitted.
2. No frame creasing or hammering permitted. You can notch or crease rear frame this is to help rear of car roll not to strengthen the frame. Frame welding is limited to front and rear bumper areas. you may do one of the following not both 1 you can weld 1 seam per side on body from firewall forward or 1 seam per side on k member with no metal added. Front frame may be shortened to front side of core support. Core support must remain in stock location.
3. If a frame section needs to be replaced or repaired (rust) you must call first. On pre-ran cars if the frame is shortened in the rear and bumper replaced the bumper shocks may not be located closer than 6" from hump plate.

4. Angles for cross member can't be longer than 5" and must be within 12" from factory location.
  5. For coil sprung cars you may use a hump plate they may be ¼" x 6" x 16" centered in the hump they will be measured from the top center of the hump and must start no lower than the center of the frame. Hump plate must be at least 2" from rear end housing. On leaf spring cars you may use a ¼" x 6" x 10" hump plate to be measured the same way. These hump plates may contour the frame or run straight across.
  6. You may clip pre-ran cars with a single butt weld with no metal added must use same make and model of frame all factory holes in frame must remain open no welding these holes shut permitted. To clip a car, you must call to get approval. Cross hump. Hump plate must remain flat plate no bending of this over the top or bottom of frame.
  7. Front mounting points on K members may be welded to body of car no more than a 3" welded area per side permitted they may be bolted solid.
  8. Sway bar and bracket may be welded to the frame this must be in stock location and must only be welded to bottom of frame.
  9. All cars may have 4 patch plates. Once plates are put on they may not be cut off and moved. These plates may be ¼" X 3" X 3" there must be a 1" space between these plates. Patch plates may not connect body to subframe or k-member.
- 

### **BUMPERS**

1. Homemade bumpers are permitted. Excessive points will not be permitted, this will be measured no exceptions. If using a factory bumper it may be loaded.
  2. Bumpers may be no lower than 14" and no higher than 20" to bottom of bumper this will be strictly enforced. Bumper seams may be welded metal may be added to bumper this must be done on the inside of the bumper front bumper only. Rear bumper may be seam welded no metal may be added to rear bumper.
  3. Bumper shocks and bumper brackets may be welded to the frame. Bumper brackets and/or shocks must be no longer than 12" in length and welded to the inside or outside of the frame. If it is welded to the outside of the frame, they must be on the side towards the outside of car. The rear bumper shocks must be mounted in the factory configuration (no angling up through the trunk floor). They will be measured from the back side of the bumper back. You can hard nose the front bumper. If no bumper shock is used, you may use a 2" x 6" x 1/4" plate to weld the bumper to the frame (2 per mounting point). These plates must be on the side of the frame. They are not permitted on the top or bottom of the frame. may You weld the shock to the frame. Factory bumper shocks can only be 12" from the end of the frame and may not be moved back on the frame. You may use 2"x 2" x 12" long square tubing for shocks.
- 

### **ENGINE / TRANSMISSION**

1. No engine cradles or protectors allowed chains on engine permitted solid or aftermarket mounts are permitted. 4 & 6 cylinder engines only.
  2. Oil pan and transmission pan may be plated the plate used may be only 1" wider than the pan they are welded to they may not connect in any way.
  3. No steel bell housings permitted.
- 

### **SUSPENSION**

1. You may modify tie rods. Valve stem protectors are permitted. A-arms must remain in stock configuration but can be plated. Any tires are permitted. Rear trailing arms may be homemade but no bigger than 2" x 2" square tubing or pipe.

2. Upper A-arms may be welded down with a 1/4" x 2" x 2" piece of steel on the front and back side of the upper A-arm and you may plug weld the center of the A-arm. Lower Aarms may not be welded. Cars do not have to bounce. Solid suspension is permitted. Coil springs in the rear may be welded, wired, or chained to the rear end. Lock shocks cannot be welded to hump plates.

3. Rear end protectors may be used but may not be used to strengthen the car in any way. Leaf spring cars may replace broken springs with factory 1/4" leaf springs only. No more than 5 springs are permitted. They must have a 2" stagger and be mounted in the factory location with 4 clamps per side. You can not change coil spring to leaf spring set ups.

4. The idler arm must be bolted factory to the frame. No bolts will be permitted all the way through the frame. The sway bar may be welded to the bottom of the frame in the factory location. You may use a 1 1/2 " x 4" bracket or a 2" square tubing or pipe to weld to the sway bar to attach to the frame. You can not move the sway bar. It must be mounted in the factory location.

5. On front wheel drive cars, you may reinforce the rear axle assembly with 2" x 2" square tubing, 2" angle or 2" wide flat plate. Factory rear subframe must remain in stock location. This may not in any way reinforce the body of the car. Nothing bigger than 2" x 2" may be used and the 2" x 2" can attach to the rear hubs. Strut tubes or all thread may be taller than the speaker deck. You are only permitted a 6" corner gusset on the rear end. Trailing arms can be mounted no further than the factory mount point.

6. 5 or 8 lug rear ends are permitted.

---

## F

---

### FRAME/FIX-IT PLATES

1. All frame/fixit plates must be square. All fresh cars are permitted a maximum of 4-4"x4"-1/4" frame plates. All pre-ran cars are permitted a maximum of 6-4"x4"-1/4" frame/fixit plates. Must have 1" gap between plates.

2. Once plates are applied, they cannot be removed or moved.

---

### QUESTIONS

**Derbydog does NOT inspect via text/phone calls. All questions or comments are due to visual inspection at event for final approval.**

Text questions will be answered to guide you to a direction in the rules for you to read.

Text Todd: (740)-648-5639