

DERBYDOG LLC

FULL-SIZE TRUCK CLASS (New for 2022)

1/3/2022

-RULES SUBJECT to CHANGE at ANYTIME-

Truck frame must be a factory 1 ton or smaller frame that came with a 6 or 8' bed. (not a box truck or straight bed)

1. Any American made truck is permitted that came with a factory 6' or 8' bed. 4-wheel drive trucks may only run 2WD (pull a driveshaft). Any STANDARD ONE TON and down is permitted. If truck frame has extra support brackets or is beefed up from the factory you better call before building and we'll come look at it! Officials decision will determine if it can be ran!! Suburban's are permitted.
2. Tailgates may be welded shut using 3"x¼" strap. A maximum of 48" of strap may be used. Back bumper or tailgate has to be 16" of the ground. No wrapping quarter panels to bumper. Doors can be welded solid with 3"x3". Driver's door can be skinned.
3. Beds must be welded to the cab of the truck with a 3" strap directly behind the doors.
4. An interior four point cage is required to compete. The cage may not extend outside of the cab into the bed. However, it may attach vertically to the frame in four locations. No metal may be added to the frame to attach the cage. The vertical bars must be welded directly to the frame.
5. Car bumpers may be used. Factory bumper brackets can be used or 3"x3" angle or square tubing 8" long.
6. A single piece of 3"x3"x¼" angle iron may be welded from the left front frame rail to the right front frame rail (in front of a-arms) on all front coil sprung trucks only. Front leaf sprung trucks may use a chain from rail to rail or from the engine cradle to each rail.
7. Trucks must securely fasten gas tanks directly behind the center of the cab in the bed. Gas tank protector can be a max 24" off back of cab and no wider than frame rails.
8. 48" piece of ¼"x2"x2" angle may be welded on inside of tailgate.

9. Fix it plate rule 6"x6"x1/4" follow car rules! If abused plate will be cut off!!!!
Can be added to fresh or pre-ran trucks.

10. NO HUMP PLATES

11. C-channel front frame trucks can run kickers off the front bar to the middle to the A arms no bigger than 2"x2" square tube. Boxed framed trucks down bars have to stop at firewall.

12. Front bumper height is 26" to bottom of bumper.

13. Homemade bumper can be max 8"x8" square tube loaded.

14. Max 10 leaf's on rear must have a 1" stager. Max 5 clamps permitted per side.

15. Factory front leaf springs only, no conversions. Must have factory brackets.

16. No bead locks.

17. 20" must be at least 20" to bottom of the rear frame.

18. No Smashing bed sides down.

19. All thread only to lock rear suspension

TRUCKS BUILT TO:

-Fair Derby, Twisted Metal, Smash-It, Hard-Core, & most all other promoters are MOST LIKELY within these rules.

THERE IS NO: PIN-to-WIN PERMITTED! NO HOLDING, TEAMING, ETC.