

DERBYDOG INC

DEMOLITION DERBY

80s & NEWER STREET STOCK FULL-SIZE STOCK MINI-VAN/TRUCK/SUV STREET STOCK COMPACT

**TRUMBULL CO FAIR
DEMOLITION DERBY 7-16-2023**

RULE BOOK DISCLAIMER

The rules and/or regulations set forth herein are designed to provide for the orderly conduct of racing and demo events and to establish minimum acceptable requirements for such event. These rules shall govern the condition of all events, and by participation in these events, all participants are deemed to have complied with these rules. **NO EXPRESSED OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM PUBLICATIONS OF OR COMPLIANCE WITH THESE RULES AND OR REGULATIONS.** They are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant, spectator, or official.

The race director shall be empowered to permit reasonable and appropriate deviation from any of the specifications herein or impose any further restrictions that in his/her opinion does not alter the minimum acceptable requirements. **NO EXPRESSED OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM SUCH ALTERATION OF SPECIFICATIONS.** Any interpretation or deviation of these rules is left to the discretion of the officials. Their decision is final.

The Management of Trumbull County Agricultural Society

-RULES SUBJECT to CHANGE at ANYTIME-

RULES ARE SIMILAR TO SMASH-IT

Other promoter's rules may be comparable

Street Stock Compact: RWD cars can be no more than 106" wheelbase and FWD cars can be no more than 112" wheelbase. No full frame cars are permitted. **NO MOTOR SWAPS PERMITTED!**

Street Stock Full: Any 1980's and newer cars. No hearses or limousines are permitted.

NO MOTOR SWAPS PERMITTED!

Mini-Van/Truck/SUV: Any 4 or 6-cylinder permitted. **NO MOTOR SWAPS PERMITTED!**

General Rules

1. Read all rules carefully and follow them!

There will be no stretching or bending of any rules or you will either run in the modified class or go home!

2. You must pass inspection within 3 times through or you will not be permitted to run.

3. A 12" x 12" roof sign is mandatory. It cannot strengthen the car in anyway.

4. Cars must be stock unless modifications are stated in the rules. Cars must have functioning brakes at all times on at least one axle. No painting of the frames, inside of body of the car, or underneath of the car and inside of the trunk.

5. A helmet, seat belt, and eye protection must be worn at all times on the track.

6. If it doesn't say you can do it, don't do it.

7. Any controversies or protests must be brought up during the drivers meeting. We have the right to re-inspect, cut, or drill any car at any time. If you are caught breaking the rules you will forfeit all winnings and/or prizes you are due. If you stretch a rule, you will lose that rule.

8. All airbags, glass, plastic, and interior must be removed before arriving to the event.

9. Any aftermarket parts must be approved. You must call and submit pictures for approval. Parts that are not approved before the derby are not permitted to run.

10. No painting of the frames, inside of the body of the car, or underneath of the car and inside of the trunk. This includes overspray. If found with paint within those areas, the car will not even be inspected.
11. All trailer hitches and braces must be removed.
12. Batteries must be moved to the passenger front floorboard. They must be properly Secured and covered.
13. Patching and rust repair will be permitted only if cleared by an official.
14. Officials' decisions are final! All cars are subjected to re-inspection at any time.
15. If the car is found to have plate on the frame or body that the rules do not allow the car will not be permitted to run. There will be no option to fix this problem.
16. If you hammer/shape/weld on the frame in any manner not covered in the rules you will not be able to run. There is no fixing this.
17. You have 1 minute to make an aggressive hit. After 1 minute that car is disqualified. That is 1-minute total. An aggressive hit is solely at the discretion of the officials
18. You are not permitted to hit anyone in the driver's door. If you do, you are disqualified. If you use your driver's door to take advantage of this rule, the car that hit you is not disqualified.
19. You may not get out of your car for any reason during the heat until you are out.
20. You are only permitted to have 1 fire in your car. This will result in a disqualification.
21. No sandbagging, teaming, or holding. Any of these will result in a disqualification. You cannot pin to win.

BUILD

1. Any gear is permitted. You must run the stock housing and axles for the make and model of the car. Rear end bracing is not permitted.
2. Cars must be 100% stock! No cross breeding the entire drive line. It must be the same make as the car (Chevy to Chevy, Ford to Ford, etc). It must have the factory engine of the make and model of the car with the stock exhaust or headers. The exhaust may be cut off.
3. The engine must be mounted with the stock mounts in the stock position. No welding of mounts. They must be bolted in. No homemade cross members. The cross member must be stock and bolted in, not welded.

4. You may leave the stock gas tank in the stock location, or you may relocate the fuel tank to the rear floor of the car. If this is done, you must use a fuel cell or boat tank. If it is a plastic fuel tank it must be bolted or welded to sheet metal in a steel structure. No stock fuel tanks are permitted inside of the car. If you move the fuel cell to the inside of the car it must be securely fastened to the floor with bolts and/or #9 wire and you must remove the stock tank from under the car. Ratchet straps are not approved to mount the fuel cell.

5. The windshield may be left in the car, but it is recommended that you remove it. The following must be removed prior to entering the fairgrounds: the windows, headlights, taillights, all the chrome, and the mirrors. The interior must be swept clean of debris and glass. You must remove all glass, plastic, and fiberglass on the outside of the car including the plastic bumper covers. **ALL AIRBAGS AND PUCKS MUST BE COMPLETELY REMOVED**

6. Under the hood you may take the plastic fender wells out. The battery may be left in the stock location. You may put a rubber mat over it or spray it with foam around it but not excessively. You may move the battery to the floor of the car. You may lengthen the cables to reach the battery on the floor but not the wiring harness. This will be strictly enforced.

7. If the car has a wiring harness in front of the core support you may move it behind the core support. You cannot remove body mount bolt to do this.

8. All body mount bolts must be factory stock. No altering is permitted. **Body and Frame must match make and year.**

9. The doors must be chained or wired in no more than 8 places per door. The wire for the bottom of the doors may go around frame. You may use 5/16" chain or 2 strands of #9 wire per hole. You can weld the driver's front door for safety using 3" x 3" x 1/4" strapping and you can have a door skin no thicker than 1/8" or similar material.

10. Trunks must be chained or wired in no more than 8 places. Two of these may go around the bumper and/or the frame. The deck lid and tailgate must be in the factory position on the car or it must be completely removed from the car. **MUST BE OPEN FOR INSPECTION!** If you removed the deck lid you are not permitted any wire for your trunk. Two (2) 8" x 8" inspection holes must be put in all deck lids within 2" of the center of the quarter panel rain channel. You cannot remove the speaker deck from the car. **SPEAKER DECK MUST REMAIN IN STOCK, UPRIGHT LOCATION.** No welding or adding metal is permitted. The deck lid is being measured 12" from the top of the rear quarter panels in the center of the deck lid in 3 spots starting from the back of the deck lid up. If you don't have a deck lid, you are not permitted any wire for your trunk. No dishing of trunk.

11. Hoods may be wired or chained in 8 spots. You may use 5/16" chain or 2 strands of #9 wire per hole. It must be sheet metal to sheet metal only. No welding washers for holes. There must be a 12" hole in the hood in case of a fire. You must remove the hood latch. Hoods must be open for inspection. A double strain of #9 wire in the center of the front windshield is mandatory.

12. Creasing of the body is permitted but it must be behind the back door on the quarter panels only. The quarter panels must stay the stock height of the car. **Quarter Panels must not be more than 70 degrees from 90 degrees upright.**

13. Any tire and rim combos are permitted. Doubled tires are permitted. No foam filled tires or bead locks. **No solid rims.**

14. You can have a safety bar behind the driver's seat if you choose. These may be no bigger than 2" x 2" and the mounting plate can be no bigger than 6" x 6" and must be mounted no farther than 6" behind the driver's seat. You may also reinforce the driver's door as you see fit for driver safety. This may be done from door seam to door seam only.

15. The car's factory springs and shocks are what can be used. **No solid suspension. No welded suspension. Screw in spring risers are permitted.** No wire, chains, or any weld on the rear ends or the rear spring pockets. **The car must bounce.**

16. Any car bumper is permitted except for Chrysler pointy bumpers. They must be bolted and welded on in the factory location. You may collapse the shocks and weld all the way around the shock and to the mounting plate to the bumper and there must be a 1½" gap between the frame and the factory bumper shock plate. The shock must be bolted in the factory location. If the car did not come with bumper shocks, you cannot add them. You can use 4" x 4" box tubing that is 1/4" thick as a bumper that is no more than 5 feet long with no point. The ends of the bumper must remain open. No metal added to the bumper is permitted. If the car has no shocks, the bumper may be welded directly to the frame with no metal added. On the back side of the bumper where the shock mounts you may use a 1/4" x 6" x 6" piece of flat metal to create a flat mounting surface. DEC bumpers and Adept Products bumpers are permitted. Homemade bumpers must be bolted together, not seam welded. **NO POINTY BUMPERS** If using square tubing for bumper, it **MUST** be wrapped, including ends.

FULL-SIZE: Front and rear bumper height: Minimum 16"-Official's Discretion on pre-ran cars.

17. You may weld the spider gears in the rear end to make it posi. You must use factory rear end housing for the car you are running.

18. FIXIT PLATE RULE: You are permitted 2 Fixit Plates on Fresh vehicles. Once pre-ran, you are permitted 2 more fixit plates. A maximum of 4 total fixit plates are permitted on pre-ran vehicles. Must have a 4" gap between Fixit Plates.

Text all questions to Jeremy Hejduk – 440-223-4723